

With Environmental Acoustics™ from

**CertainTeed**  
ceilings

certainteed.com/  
ceilings

# WALLS & CEILINGS

June 2012 | Volume 75, Issue 6 | The Voice of the Industry Since 1938™ | www.wconline.com

A bnp PUBLICATION

MANUFACTURER'S SPOTLIGHT

## QUIKRETE

Base Coat Stuccos, Decorative Finishes and Structural Repair Products



Since 1940, The QUIKRETE Companies has manufactured consistent, high quality commercial grade wall systems for residential and commercial construction.

With more than 95 manufacturing locations throughout the United States, Canada and Puerto Rico, The QUIKRETE Companies offers a complete line of reliable, cost-effective and innovative base coat stuccos, decorative finishes and structural repair products.

The line—designed for one-, two- and traditional three-coat applications—is available in 80 pound bags and 3,000 pound bulk bags with silo delivery systems.

### SCRATCH AND BROWN BASE COAT STUCCO

This contractor grade, Portland cement-based, pre-blended stucco designed to be used as the scratch and brown coat in a three-coat stucco application, or the brown coat in a two-coat application. The specially designed stucco is intended for use over code-approved metal lath or solid bases such as masonry, cast-in-place or pre-cast concrete. QUIKRETE Base Coat Stucco can be trowel or spray applied and provides consistency from bath to bath.

### BASE COAT STUCCO WITH WATER-STOP

This Portland cement based stucco is designed to be used as the scratch and brown coat in a three-coat stucco application, or the brown coat in a two-coat application. It contains special additives which prevent premature loss of mixing water, increase workability and allow the stucco to develop water repellant properties as it cures. The water repellency prevents excessive absorption from wind-driven rain.

### BASE COAT STUCCO WITH PUMP GRADE

This fiber-reinforced, Portland cement-based stucco is designed for use as the scratch and/or brown coat in a three-coat stucco application. Formulated with special additives, it prevents the premature loss of mixing water during pumping procedures and provides increased working time.

### ONE COAT FIBERGLASS REINFORCED STUCCO (FRS)

This is an alkali-resistant glass fiber-reinforced stucco intended to be used as a one-coat stucco over exterior rigid insulation board or non-insulated exterior approved sheathing, including Type-X gypsum board. The product is applied at a minimum thickness of 3/8 inch to 1/2 inch and can be textured as desired and provides a high-impact, crack-resistant shell. The stucco is approved for a one-hour fire rated wall assembly over plywood and EPS foam or OSB and EPS foam.

### FINISH COAT STUCCO

This Portland cement based finishing plaster is designed for use as a decorative finish over Portland cement base coats or QUIKRETE One Coat Fiberglass Reinforced Stucco. The stucco can be applied at 1/8 inch thickness using a trowel or spray application. Surface textures can be achieved with a brush or a trowel when the mix is still plastic and workable. The mix is available in gray or white, and can be colored with liquid or dry pigments. Twenty standard liquid stucco colors are available.

For more information, visit [www.quikrete.com](http://www.quikrete.com).

