

CONCRETE REPAIR

PRODUCT No. 8620-10, -12, -13

DIVISION 3

07 92 00 Joint Sealants

PRODUCT DESCRIPTION

QUIKRETE® Concrete Repair is a superior crack filler and sealer for repairs to vertical and horizontal concrete, masonry and stucco surfaces up to 1/2 in (13 mm) wide. The textured acrylic formula is designed to blend in with the color and texture of concrete surfaces. QUIKRETE® Concrete Repair provides excellent adhesion and remains flexible for durable repairs.

PRODUCT USE

QUIKRETE® Concrete Repair fills and repairs cracks up to 1/2 in (13 mm) wide in concrete, masonry, stucco, sidewalks, patios and driveways. Benefits include:

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

SIZES

QUIKRETE® Concrete Repair is available in the following tube sizes:

- 5.5 fl oz (162 mL) squeeze tubes
- 10 fl oz (295 mL) standard caulking tubes

YIELD

- 5.5 fl oz (163 mL) tubes will yield 13 linear feet (3.9 m) at a 1/4 in (6.3 mm) bead.
- 10 fl oz (295 mL) tubes will yield 24 linear feet (7.3 m) at a 1/4 in (6.3 mm) bead.

INSTALLATION

SURFACE PREPARATION

Surface must be clean and dry, and free of oil and grease. Clean all dirt, dust, and loose or chipped pieces of concrete from the crack before filling. Cracks narrower than 1/8 in (3.2 mm) wide should be chiseled at least this wide prior to application.

APPLICATION

Cut tip of cartridge on an angle to make a 1/4 in to 3/8 in (6.3 mm to 9.5 mm) hole. Use 10 fl oz (295 mL) cartridge in standard caulking gun. Fully puncture airtight foil seal at the base of the tip. Apply by pushing cartridge over surface and forcing a bead of QUIKRETE® Concrete Repair deep into the crack. Apply no thicker than 3/8 in (9.5 mm) in one application. On horizontal surfaces, deep cracks can be partially filled with sand prior to application. QUIKRETE® Concrete Repair can be tooled to even out the surface. Excess material may be cleaned with a damp cloth.



PRECAUTIONS

- In most cases, repair materials will not be an exact color match to material being repaired.
- Do not use to fill control/expansion joints.
- Do not use for structural repairs. Wait at least 24 hours before painting.
- Use latex paints only.
- Air and surface temperature should be above 40 °F (4 °C) for proper application.
- Do not apply if rain threatens or is predicted within 12 hours.
- Store between 35 °F and 100 °F (2 °C and 38 °C).
- Do not allow to freeze.
- Do not apply where temperatures may reach 140 °F (60 °C) or higher (fireplaces, electric wires, etc.).

SAFETY

IMPORTANT: Read Safety Data Sheet carefully before using. **WEAR IMPERVIOUS GLOVES**, such as nitrile, mask and eye protection. **WARNING:** May irritate skin and eyes. May be harmful if swallowed. **KEEP OUT OF REACH OF CHILDREN**

WARRANTY

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured by or under the authority of The Quikrete Companies, LLC. © 2022 Quikrete International, Inc.