



CEMENT &amp; CONCRETE PRODUCTS™

**ANCHORING EPOXY****MATERIAL SAFETY DATA SHEET**  
(Complies with OSHA 29 CFR 1910.1200)**SECTION I: PRODUCT IDENTIFICATION**

The QUIKRETE® Companies  
One Securities Centre  
3490 Piedmont Road, Suite 1300  
Atlanta, GA 30329

Emergency Telephone Number  
(770) 216-9580

Information Telephone Number  
(770) 216-9580

MSDS X4  
Revision: Aug-12

**QUIKRETE® Product Name**

QUIKRETE® FASTSET™ ANCHORING EPOXY  
QUIKRETE® HIGH STRENGTH ANCHORING EPOXY  
QUIKRETE® DOT ANCHORING EPOXY

**Code #**

8620-30  
8620-31  
8620-36, -37

**Part A**

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION Safety Glasses, Gloves	

**Part B**

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION Safety Glasses, Gloves	

**Product Use:** Two component epoxies for general construction

**SECTION II - HAZARD IDENTIFICATION**

**Known Hazards:** **Part A:** Skin and eye irritation. Sensitizer; **Part B:** Corrosive

**Signs and Symptoms of Exposure:** **Part A:** Eyes: Irritation. Corneal injury is not expected. Skin: Irritation. Can cause allergic skin reactions in susceptible individuals, e.g. itching, redness, swelling, etc. Inhalation: No ill effects expected. Heated vapors can cause irritation. **Part B:** Eyes: Irritation. Possible eye burns. Skin: Can cause irritation and skin burns. Inhalation: No ill effects expected. Heated vapors can cause irritation.

**Medical Conditions Aggravated by Exposure:** Skin, eye, and respiratory conditions

**Routes of Exposure:** Dermal. Inhalation.

**Carcinogenicity:** This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.

**SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Part A: Hazardous Component	CAS #	% By Weight	PEL	TLV	STEL
Diglycidyl Ether of Bisphenol A	25085-99-8	> 40%	NE	NE	NE
Titanium Dioxide	13463-67-7	<10	NE	5mg/m <sup>3</sup>	NE
Part B: Hazardous Component	CAS #	% By Weight	PEL	TLV	STEL
n-aminoethylpiperazine	140-31-8	10% – 30%	NE	NE	NE
Nonyl phenol-	84852-15-3	10% – 30%	NE	NE	NE

---

**SECTION IV – First Aid Measures**

---

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Wash with mild soap and water. Launder contaminated clothing before reuse.

**Ingestion:** If conscious, give plenty of water; do not induce vomiting unless directed to by a physician. Call a physician.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If Sensitization occurs, future contact with the material should be avoided.

---

**SECTION V - FIRE AND EXPLOSION HAZARD DATA**

---

**Flash Point:** Part A: > 300° F. Part B: > 200° F

**Flammable Limits:** N/A

**Extinguisher Media:** Carbon Dioxide, Dry Chemical, Water Spray, Foam

**Special Fire Fighting Procedures:** Use a self-contained breathing apparatus when fighting fires involving chemicals.

**Unusual fire and Explosion Hazards:** None known. Thermal decomposition products can be formed.

---

**SECTION VI – ACCIDENTAL RELEASE MEASURES**

---

Avoid all personal contact, scoop up with spade and place in disposable metal container. Flush contaminated areas.

---

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE**

---

Avoid contact with eyes, skin and clothing. Avoid prolonged inhalation of vapors. Use with adequate ventilation. Wash thoroughly after handling. Store in a cool dry place out of direct rays of the sun. Keep from freezing. Recommended storage temperature range in between 40° and 95° F.

---

**SECTION VIII – EXPOSURE CONTROL MEASURES**

---

**Respiratory Protection:** None normally required. Use a NIOSH –approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Ventilation:** General (natural or mechanical induced fresh air movements)

**Eye Protection:** Wear splash proof chemical goggles

**Protective Gloves:** Cloth or impermeable (neoprene or rubber) gloves

**Other Protective Clothing or Equipment:** Wear appropriate apparel to prevent skin contact

---

**SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS**

---

**CEMENT & CONCRETE PRODUCTS™**

	<b>Part A:</b>	<b>Part B:</b>
<b>Appearance:</b>	White Paste	Black Paste
<b>Odor:</b>	Slight Odor	Slight Amine Odor
<b>Vapor Density:</b>	Non-volatile	Non-volatile
<b>VOC Content:</b> 0 g/l		

---

**SECTION X - REACTIVITY DATA**

---

**Hazardous Polymerization:** Will not occur

**Stability:** Stable

**Incompatibility:** Strong acids, peroxides, and other oxidizing agents

**Hazardous Decomposition Products:** Thermal decomposition can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

**Conditions to Avoid:** Exposure to excessive heat and storage above 95° F will shorten shelf life.

---

**SECTION XI – TOXICOLOGICAL INFORMATION**

---

**Part A:**

Acute Oral Toxicity: LD50: > 2,000 mg/kg

Acute Dermal Toxicity: LD50: > 2,000 mg/kg

**Chronic Health Hazard:** Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

**Developmental Toxicity:** Resins based on the diglycidyl ether of bisphenol A (DGEBA) did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

**Reproductive Toxicity:** In animal studies, did not interfere with reproduction.

**Genetic Toxicology:** In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

**Potential Health Effects:**

*Inhalation:* Not expected to be a relevant route of exposure, however, under conditions where exposure to vapors or mists is possible, could cause respiratory tract irritation.

*Skin:* May be mildly irritating to the skin. Contact with hot material can cause thermal burns which may result in permanent damage. May cause skin sensitization.

*Eyes:* May be mildly irritating to the eyes. Contact with hot material can cause thermal burns which may result in permanent damage or blindness.

*Ingestion:* Not likely to be a relevant route of exposure.

**Part B:**

Eye irritation/corrosion: Eye irritation.

**Acute dermal irritation/corrosion:** Moderate skin irritation.

**CEMENT & CONCRETE PRODUCTS™**

**Sensitization:** May cause sensitization by skin contact. Sensitization has occurred in laboratory animals after repeated exposures.

**Oral:** LD50 2.15 g/kg (rat) slightly toxic

**Inhalation:** Not determined.

**Dermal:** LD50 .90 g/kg (rabbit) moderately toxic

**Skin:** (Draize) 8.00 /8.0 (rabbit) corrosive

**Eyes:** (Draize) Believed to be > 80.00 - 110.00 /110 (rabbit) extremely irritating

**Sensitization:** (Buehler) Negative - skin (guinea pig)

---

**SECTION XII – ECOLOGICAL INFORMATION**

---

**Ecotoxicity:** Not Available

**BOD5 and COD:** Not Available

**Products of Biodegradation:** Not available

**Toxicity of the Products of Biodegradation:** Not available

**Special Remarks on the Products of Biodegradation:** Not available

---

**SECTION XIII – DISPOSAL CONSIDERATIONS**

---

**Waste Disposal Method:** If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

**SECTION XIV – TRANSPORT INFORMATION**

---

**DOT Shipping Information:** Consumer commodity, ORM-D

**IMDG Shipping name:** Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III, Ltd Qty

**IATA Shipping name:** Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

---

**SECTION XV – OTHER REGULATORY INFORMATION**

---

**US OSHA 29CFR 1910.1200:** Considered non-hazardous under this regulation

**SARA (Title III) Sections 311 & 312:** Not listed

**SARA (Title III) Section 313:** Not subject to reporting requirements

**TSCA (May 1997):** All components are on the TSCA inventory list

**Federal Hazardous Substances Act:** Considered non-hazardous under this regulation

**California Proposition 65: WARNING:** Sanding, cutting, or grinding these products will expose you to chemicals known to the State of California to cause cancer.

**Canadian Environmental Protection Act:** Not listed

**Canadian WHMIS:** This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

---

**SECTION XVI – OTHER INFORMATION**

---

**CEMENT & CONCRETE PRODUCTS™****Abbreviations:**

PEL = OSHA Permissible Exposure Limit

TLV = ACGIH Threshold Limit Value

C = Ceiling

STEL = Short Term Exposure Limit

NE = None Established

NA = Not Applicable

ND = Not Determined

ppm = parts per million

<b>HMIS-III:</b>	Health –	0 = No significant health risk
		1 = Irritation or minor reversible injury possible
		2 = Temporary or minor injury possible
		3 = Major injury possible unless prompt action is taken
		4 = Life threatening, major or permanent damage possible
	Flammability-	0 = Material will not burn
		1 = Material must be preheated before ignition will occur
		2 = Material must be exposed to high temperatures before ignition
		3 = Material capable of ignition under normal temperatures
		4 = Flammable gases or very volatile liquids; may ignite spontaneously
	Physical Hazard-	0 = Material is normally stable, even under fire conditions
		1 = Material normally stable but may become unstable at high temps
		2 = Materials that are unstable and may undergo react at room temp
		3 = Materials that may form explosive mixtures with water
		4 = Materials that are readily capable of explosive water reaction

**Last Updated: August 22, 2012**

**NOTE:** The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. END OF MSDS.