

**CEMENT & CONCRETE PRODUCTS™** 

# **BLACKTOP CRACK SEAL**

PRODUCT NOS. 8640-05

## PRODUCT DESCRIPTION

QUIKRETE® Blacktop Crack Seal is uniformly blended latex e formulated to fill cracks in horizontal asphalt surfaces.

#### **PRODUCT USE**

QUIKRETE® Blacktop Crack Seal is formulated to fill cracks on any horizontal asphalt surface. Blacktop Crack Seal will also bond to concrete. There is nothing to add. Just shake the ready-to-use product and pour directly from the container. The product blends in with the natural charcoal color of aged blacktop.



• QUIKRETE® Blacktop Crack Seal is available in 5.5 ounce (163 ml) squeeze tubes, one quart (946 ml) and one gallon (3.8 L) plastic bottles.

#### **YIELD**

• One quart (946 ml) bottle will fill a 1/4" x 1/2" (6 x 12 mm) crack 38' (11.6 M) long

#### **INSTALLATION**

#### **SURFACE PREPARATION**

Shake well before using. Clean all loose dirt, dust and gravel from the crack. Surfaces to receive Blacktop Crack Seal should be free of oil and grease. Cleaning with QUIKRETE® Concrete & Asphalt Cleaner (#8601) is recommended to insure the best bond. If the crack is deeper than ¼" (6 mm), use backer rod or sand to fill the crack to within ¼" (6 mm) of the surface.

#### **APPLICATION**

Cut the tip of the spout to make a ¼" (6 mm) to 3/8" (9 mm) hole. Squeeze Blacktop Crack Seal into the crack, over-filling slightly to allow for shrinkage. A second coat can be applied after 24 hours as needed to provide a uniform finished surface.



### **PRECAUTIONS**

• Do not apply in cracks wider than ½" (12 mm). Temperature should be between 45°F and 100°F (7°C and 38°C). Keep product from freezing. Do not apply if rain is expected within 24 hours. Do not apply to surfaces which will later be coated with anything other than acrylic water-based paint.

#### WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at

www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.

# **DIVISION 32**

Flexible Pavement Repair 32 01 17

\* Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifical