

BUILDING ON YOUR CONCRETE SALE

Your customer's request for QUIKRETE® Concrete Mix is not the end of the sale..... it's just the beginning! QUIKRETE® can help you turn your concrete mix sale into a more profitable transaction that will also provide your customer with a better finished project.

(No. 1101)



UPSELL TO THESE HIGHER MARGIN PRODUCTS

MAKE YOUR TOTAL SALE MORE PROFITABLE WITH THESE "ADD ON ITEMS"



FAST-SETTING CONCRETE MIX (No. 1004)

Sets hard in approximately 20-40 minutes. Sets posts without mixing. Pour dry mix into hole and soak with water.

Use For Setting:

- Fence posts
- Mailbox posts
- Swing sets

Use For Building:

- Steps
- Sidewalks
- Air conditioner pads

CRACK RESISTANT CONCRETE MIX (No. 1006)

Formula significantly reduces cracking from drying shrinkage and is designed for use in structural concrete applications. **Other benefits & features include:**

- Superior workability
- Provides greater impact resistance
- Air entrained for improved freeze-thaw durability
- Eliminates the need for wire mesh in typical slab-on-grade slabs



QUIKRETE® 5000 CONCRETE MIX (No. 1007)

Designed for higher-early strength gain. Achieves 2500 PSI in 3 days and 5000 PSI in 28 days. Ideal for cold weather application. **Use For:**

- Concrete projects 2" thick or more that require high strength
- Driveway aprons
- Patios
- Deck supports
- Curbs
- Floors



EXPANSION JOINT STRIPS (No. 6917)

Expansion joint filler used to prevent damage during expansion and contraction of concrete. Weather resistant. **Use for:**

- Driveways, sidewalks and patios
- Between concrete slabs and to separate slabs from structures



ACRYLIC CONCRETE CURE & SEAL - SATIN FINISH (No. 8730)

Water based clear acrylic coating cures freshly placed concrete and seals concrete and masonry surfaces.

- Eliminates the need for water curing freshly placed concrete.
- Protects and seals from acids, grease, oils, food stains, salt and more.



LIQUID CEMENT COLORS (No. 1317)

Mix with water and then add to dry concrete mix. One bottle will mix with two 80 lb. or 60 lb. bags of Concrete Mix. Available in red, brown, buff, charcoal and terra cotta. Provides permanent integral color



POLYURETHANE SELF-LEVELING SEALANT (No. 8660)

A high performance, construction grade, polyurethane sealant, used for sealing cracks and joints in horizontal concrete surfaces.

Use For:

- Sealing expansion joints in concrete slabs
- Sealing cracks in concrete floors, driveways, patios, steps, basements and pool decks



CONCRETE BONDING ADHESIVE

Permanently bonds new concrete to existing concrete overlays 1" or thicker. Eliminates the need for roughing the surface before the application.



GUIDE TO CONCRETE BOOK (No. 6924)

The QUIKRETE® GUIDE TO CONCRETE book provides practical instructions and clear step-by-step photos to help accomplish the most popular projects and repairs made with concrete, masonry and stucco products.