



CEMENT & CONCRETE PRODUCTS™

CONCRETE & MASONRY HIGH GLOSS SEALER

PRODUCT NO. 8800-06

DIVISION 3

Maintenance of Concrete
03 01 00

PRODUCT DESCRIPTION

QUIKRETE® Concrete & Masonry High Gloss Sealer is a water-based, high gloss, acrylic clear sealer designed to waterproof, seal and enhance the color of decorative concrete, masonry, pavers, brick and natural stone surfaces. The high gloss sealer repels water and protects from oil, gasoline, grease, salts, acids, household chemicals, food stains and is UV resistant. For interior or exterior use.

PRODUCT USE

QUIKRETE® Concrete & Masonry High Gloss Sealer is a highly water resistant clear, glossy coating designed to water proof, seal and enhance the color of decorative concrete, masonry, pavers, brick and natural stone surfaces. QUIKRETE® High Gloss Sealer is UV Resistant.

SIZES

- 1 gal (3.8 L) bottle
- 5 gal (18.9 L) pail

COVERAGE

Apply at 200-400 sq ft per gallon (18-37 M²). Coverage will depend on porosity of surface.

PHYSICAL PROPERTIES

Typical physical properties of QUIKRETE® High Gloss Sealer are identified in Table 1.

TABLE 1 TYPICAL PHYSICAL PROPERTIES

Solids Content	25% wt.
Drying time (50-90° F / 10-32°C)	Approx. 2 hour
Volatile Organic Compound (VOC)	90 g/L maximum

INSTALLATION

SURFACE PREPARATION

New concrete: Allow a minimum of 30 days for new concrete to cure before applying High Gloss Sealer.

Existing surfaces: Surface must be clean and dry. Oil stains, dirt and other contaminants must be removed. Use QUIKRETE® Concrete and Asphalt Cleaner (No. 8601) or QUIKRETE Oil Stain Remover (No. 8670-06) to properly prepare the surface. Unsound or flaking concrete should be removed or repaired.



Previously sealed surfaces: Surface must be cleaned, porous and able to accept additional sealer. Do not use this product on non-porous, sealed or painted surfaces. To test, place drops of water on the surface. If the water is absorbed, the surface is porous enough to accept the sealer.

APPLICATION

QUIKRETE® Concrete & Masonry High Gloss Sealer is ready-to-use and can be applied with a roller or brush. Apply in a uniform thickness to obtain coverage of 200-400 sq. ft (18-37 M²) per gallon. Coverage will vary depending on surface texture and porosity. A second coat can be applied after 2 hours. Wipe off excess sealer from surface before it dries. Clean up with warm, soapy water.

PRECAUTIONS

- Do not apply if raining, heavy dew or temperatures below 50°F (10°C) are expected within 24 hours. Do not seal areas prone to standing water. Keep from freezing. Do not apply more than recommended amount.
- Solvents and cleaners containing solvents, such as pine or citrus, will discolor.

WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305
(404) 634-9100 • Fax: (404) 842-1425

* Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications