

**Project****Sealing Concrete and Masonry**

QUIKRETE® Commercial Grade Concrete Sealer forms a tough, water-resistant finish that is virtually unaffected by exposure to water, common acids, alkalis, petroleum, solvents, oils, greases, and salts. QUIKRETE® Concrete Sealer quickly penetrates the surface of concrete, flagstone, or unglazed tile to harden, protect and preserve the material. Use it to seal walks, driveways, garage floors, concrete porch decks, steps, patios, exposed aggregate finishes, and any other concrete surface exposed to weather and harsh environments.

**Required Tools & Materials**

- QUIKRETE® Commercial Grade Concrete Sealer
- QUIKRETE® Concrete & Asphalt Cleaner
- Scrub brush
- Broom
- Paintbrush
- Roller Mop or squeegee
- Clean container

Step by Step**Surface Preparation**

1. Remove all wax, oil, grease, dirt and dust from the surface to be sealed. Use QUIKRETE® Concrete & Asphalt Cleaner, as needed.
2. Allow the surface to dry completely before applying sealer.

Application

1. Pour the QUIKRETE® Concrete Sealer slowly into a clean container. Stir gently but thoroughly to mix. Rigorous stirring can form air bubbles in the sealer, which could affect the final finish.
2. Apply a small amount of sealer to an inconspicuous area to ensure aesthetic compatibility.

3. Apply to the dry surface full strength, using a brush, roller, mop or squeegee.

4. In most cases, one coat provides sufficient protection. Very porous surfaces may require two coats. Allow to dry 2 hours between coats.

For Best Results

- Do not apply at temperatures below 40° F.
- Do not apply if rain is likely. Never thin QUIKRETE® Concrete Sealer with water solvents.

The QUIKRETE® Companies