

# CONCRETE & MASONRY WATERPROOFING SEALER

PRODUCT No. 8800-05

**DIVISION 3**

Maintenance of Concrete  
03 01 00

## PRODUCT DESCRIPTION

QUIKRETE® Concrete & Masonry Waterproofing Sealer is a water-based, silane-siloxane formulation designed to waterproof and seal concrete, masonry, brick, pavers, and stucco surfaces. QUIKRETE® Waterproofing Sealer repels water and protects from oil, gasoline, grease, salts and UV rays without changing the appearance of the substrate.

## PRODUCT USE

QUIKRETE® Concrete & Masonry Waterproofing Sealer is a highly water resistant, non-film-forming, penetrating sealer for interior or exterior, horizontal or vertical surfaces that allows the natural beauty of the surface to come through. QUIKRETE® Waterproofing Sealer is particularly suitable for decorative, stained or exposed-aggregate concrete and for natural stone, bricks and pavers. Resists water, deicing salts, and gasoline.

## SIZES

- 1 gal (3.8 L) bottle
- 5 gal (18.9 L) pail

## COVERAGE

Apply at 75-150 sq ft per gallon (7-14 M2). Coverage will depend on porosity of surface

## PHYSICAL PROPERTIES

Typical physical properties of QUIKRETE® Waterproofing Sealer are identified in Table 1.

**TABLE 1 TYPICAL PHYSICAL PROPERTIES**

Solids Content	7% wt.
Drying time (50-90° F / 10-32°C)	Approx. 1 hour
Volatile Organic Compound (VOC)	21 g/L maximum

## INSTALLATION

### SURFACE PREPARATION

**New concrete:** Allow a minimum of 30 days for new concrete to cure before applying Waterproofing Sealer.

**Existing surfaces:** Surface must be clean and dry. Oil stains, dirt and other contaminants must be removed. Use QUIKRETE® Concrete and Asphalt Cleaner (No. 8601) to properly prepare the surface. Unsound or flaking concrete should be removed or repaired.



**Previously sealed surfaces:** Surface must be cleaned, porous and able to accept additional sealer. Do not use this product on non-porous, sealed or painted surfaces. To test, place drops of water on the surface. If the water is absorbed, the surface is porous enough to accept the sealer.

## APPLICATION

QUIKRETE® Concrete & Masonry Waterproofing Sealer is ready-to-use and can be applied with a roller, brush or a garden sprayer. Apply in a uniform thickness to obtain coverage of 75-150 sq. ft (7-14 M<sup>2</sup>) per gallon. Coverage will vary depending on surface texture and porosity. A second coat can be applied while the first coat is still wet after 5-10 minutes. Wipe off excess sealer from surface before it dries. Clean up with warm, soapy water.

## PRECAUTIONS

- Do not apply if raining, heavy dew or temperatures below 50°F (10°C) are expected within 24 hours. Do not seal areas prone to standing water. Keep from freezing. Do not apply more than recommended amount.

## WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies  
One Securities Centre  
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305  
(404) 634-9100 • Fax: (404) 842-1425

\* Refer to [www.quikrete.com](http://www.quikrete.com) for the most current technical data, MSDS, and guide specifications