



CEMENT & CONCRETE PRODUCTS™

DIVISION 9

Coatings for Concrete &
Masonry 09 98 00

TEXTURED ACRYLIC CONCRETE COATING

PRODUCT NO. 8730-06

PRODUCT DESCRIPTION

QUIKRETE® Textured Acrylic Concrete Coating is a premium textured acrylic coating. It is designed to beautify and provide a durable, non-slip, wear surface on new or existing concrete surfaces.



PRODUCT USE:

The easy-to-apply coating is ideal for use on concrete driveways, patios, sidewalks, steps and ramps. Textured Acrylic Concrete Coating is suitable for interior or exterior use and has superior hiding characteristics.

COVERAGE/THINNING:

Covers up to 100-150 sq. ft. (9.3-13.9 m²) per gallon depending on porosity and texture. No thinning appropriate under normal conditions.

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in 30-60 minutes. Above 80°F (27°C) if needed a small amount of water may be added to maintain a reasonable working time. Suitable for foot traffic in 3-4 hours; Automobile traffic in 24 hours; Parking in 72 hours.

SURFACE PREPARATION:

General: Allow new concrete or repairs to cure for 28 days prior to application of QUIKRETE® Textured Acrylic Concrete Coating. Areas where ponding water is evident should be leveled prior to application. This product is not designed for water tanks. All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. The surface may be cleaned with QUIKRETE® Cleaner, Etcher, & Degreaser (No. 8675-34). Follow all package instructions including rinsing.

Previously Painted Surfaces: Use a tape test to ensure existing paint is well bonded. Press heavy-duty tape (e.g. duct tape) at various places on the painted surface. Pull the tape quickly from the surface. If the previous paint is removed by the tape, the paint must be removed before using this product. **Note:** Removal of lead-based paint requires special safety precautions.

APPLICATION:

WEAR IMPERVIOUS GLOVES, such as nitrile. Mix thoroughly before and during use. Apply with a premium quality roller. Spread

product evenly and finish with long, even strokes in one direction. Edges may be cut in with a good quality paint brush. If a second coat is desired, it may be applied one hour after the first coat is dry to the touch, often in 3 hours, depending on the temperature and humidity. Do not apply if temperatures below 50°F are expected within 6 hours. May not be top-coated with solvent or oil based paint.

CLEAN UP:

Clean equipment and spills while the product is wet. Cleans up with warm, soapy water.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Store between 40°F and 90°F (4°C and 32°C). In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of used absorbent, container and/or unused contents in accordance with local, state and federal regulations.

FIRST AID:

IMPORTANT! Read before using.

WEAR IMPERVIOUS GLOVES, such as nitrile.

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.

IF INHALED: If affected by vapor or mist, move to fresh air. If breathing difficulty continues, get medical attention.

IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.

WARNING: CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist or dust generated in sanding. If using indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH

approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use.

WARNING: This product contains chemicals known to the State of California to cause cancer. This product contains silica sand for texture.

VOC 90 g/L of coating less water and less exempt compounds; Meets VOC requirements in all locations; Do not thin.

Safety Data Sheets (SDS) are available at www.quikrete.com

WARRANTY

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.

** Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications*