

TRANSLUCENT CONCRETE STAIN

PRODUCT NO. 7215-00, -01, -02, -03, -04, -05, -06, -07

PRODUCT DESCRIPTION

QUIKRETE® Translucent Concrete Stain is a water-based polymer bonded concrete and masonry stain. Semi-transparent appearance highlights the natural variations in concrete and masonry surfaces. It is UV and weather resistant.

PRODUCT USE:

QUIKRETE® Translucent Concrete Stain is designed for beautifying a wide variety of concrete surfaces.

- Patios, Driveways, Pool Decks Sidewalks Basements and Interior Floors
- Available in Red (-00), Terra Cotta (-01), Cola (-02), Light Gray (-03), Light Brown (-04), Blue (-05), Brick Red (-06) and Golden Wheat (-07)

COVERAGE/THINNING: One Gallon (3.8 L) will cover 200-400 sq. feet (18.6-37.2 m²) depending on surface porosity and application technique.

DRY TIMES: Typically dries to the touch in 4 hours, depending on the temperature and humidity.

GENERAL: Apply only when surface and air temperatures are 50-90°F (10-32°C)

SURFACE PREPARATION: Concrete must be cured for 28 days before application. All surfaces must be clean and free of all dirt, dust, grease, oil, form release compounds or contaminants. Do not apply over existing paint or sealer. The surface may be cleaned with QUIKRETE® Bond-Lok™ Cleaner, Etcher, & Degreaser (No. 8675-34). Follow all package instructions including rinsing.

APPLICATION: WEAR IMPERVIOUS GLOVES, such as nitrile. Shake vigorously. Apply the stain with a brush, sponge or plastic sprayer. Do not over-apply and do not allow the product to puddle. Spread product evenly. Allow the floor to dry thoroughly. Different application techniques may result in different final appearances. If desired, a second coat may be applied one hour after surface is dry to the touch, typically in 4 hours. Allow 24 hours after staining for light use, 72 hours for automobile traffic. Clean equipment and spills while the product is wet. Cleans up with warm, soapy water. Do not apply if rain, heavy dew or temperatures below 50°F (10°C) are expected within 8 hours. Solvents and cleaners containing solvents such as pine and citrus will discolor.



To enrich the color and protect the stained surface, also apply QUIKRETE® Wet Look High Gloss Sealer (#8800-06), which may be applied one hour after the QUIKRETE® Translucent Concrete Stain is dry to the touch.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Store between 40°F and 100°F (4°C and 38°C). In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of used absorbent, container and/or unused contents in accordance with local, state and federal regulations.

WARNING: May cause eye and skin irritation. Avoid breathing spray mist or dust generated in sanding. If using indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use.

VOC 7g/L of coating less water and less exempt compounds; Meets VOC requirements in all locations; Do not thin.

Safety Data Sheets (SDS) are available at www.quikrete.com

WARRANTY

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.

