

PRODUCT LINE GUIDE:

**DIVISION 7 > 07 11 16 > CEMENTITIOUS DAMP PROOFING**

**Heavy Duty Masonry Coating >> Product No. 1312-Grey, 1301-White**



**DESCRIPTION >> PRIMARY USE**

QUIKRETE® Heavy Duty Masonry Coating is a powdered, Portland cement based on coating designed for use in damp-proofing and beautifying concrete and masonry walls. It adheres to the surface in a manner that allows it to become part of the masonry it covers. It is for use inside or outside, both above and below grade. It will withstand extreme heat, moisture and cold, and is suitable for any climate. It is recommended for damp-proofing brick, black stone, stucco and poured-in-place concrete walls.

**BRUSHABLE**

**Compressive strength, ASTM C109**

1 day	2000 psi (13.8 MPa)
7 days	5000 psi (34.5 MPa)
28 days	6000 psi (41.3 MPa)

**Flexural strength, ASTM C348**

1 day	450 psi (3.1 MPa)
7 days	550 psi (3.8 MPa)
28 days in air	1000 psi (6.9 MPa)

**TROWELABLE**

**Compressive strength, ASTM C109**

1 day	3000 psi (20.7 MPa)
7 days	6000 psi (41.3 MPa)
28 days	8000 psi (55.1 MPa)

**Flexural strength, ASTM C348**

1 day	550 psi (3.8 MPa)
7 days	650 psi (4.5 MPa)
28 days in air	1200 psi (8.3 MPa)

**SIZE AVAILABILITY**

- 40 lb (18.2 kg) bags
- 20 lb (9.1 kg) bags

**COLORS**

- Gray
- White



PRODUCT LINE GUIDE:

**DIVISION 7 > 07 92 00 > JOINT SEALANT**

***Polyurethane Self-Leveling Sealant >> Product No. 8660-30, 8660-10***



**DESCRIPTION >> PRIMARY USE**

QUIKRETE® Polyurethane Self-Leveling Sealant is a superior self-leveling, one-component, permanently flexible polyurethane multi-purpose product ideal for sealing and bonding common building materials. It offers primerless adhesion to most common materials in the building intensity. It has been specifically developed for flowing into horizontal crevices and ideal for general purpose horizontal sealing applications. It is non-staining, resistant to moisture and staining and has virtually no shrinkage. It may be used for:

- Waterproofing horizontal expansion joints in sidewalks, driveways, industrial floors, parking decks, etc.
- A variety of general purpose joint sealing applications
- End dams in glazing systems
- Flashing and below grade waterproofing membranes

**COLORS**

- Gray
- Sandstone (8660-31) only available in 29.1 oz (858 ml)

**SIZE AVAILABILITY**

- 10.1 oz (300 mL) caulk tubes
- 29.1 oz (868 mL) caulk tubes

***Polyurethane Non-Sag Sealant >> Product No. 8660-11***



**DESCRIPTION >> PRIMARY USE**

QUIKRETE® Polyurethane Non-Sag Sealant is a one-component, permanently flexible, multi-purpose polyurethane sealant. It cures in the presence of atmospheric moisture to provide a permanently elastic bond to fasten materials, which have dissimilar coefficients of expansion. It is ideal for general purpose sealing applications. It may be used for:

- Vertical or horizontal expansion joints in concrete, stucco or masonry
- Caulking around window and door openings
- Sealing skylights and chimney flashings
- Waterproofing cracked concrete

**SIZE AVAILABILITY**

- 10.1 oz (300 ml) caulk tubes

***Polyurethane Construction Adhesive >> Product No. 9902-10***



**DESCRIPTION >> PRIMARY USE**

QUIKRETE® Polyurethane Construction Adhesive is a one-component, fast cure and permanently flexible material, which cures in the presence of atmospheric moisture to provide a permanently elastic bond to fasten materials, which have dissimilar coefficients of expansion. It has excellent adhesion to concrete, masonry, stucco, pre-painted metal, plywood, glass, aluminum, steel and many plastics and composites. It may be used for:

- Repairing broken concrete
- Fastening wood, polystyrene insulation, metal or glass to concrete or masonry
- Fastening wood paneling to dry wall, concrete or masonry surfaces
- Bonding subfloors to floor joints

**SIZE AVAILABILITY**

- 10.1 oz (300 ml) caulk tubes

