

PRODUCT LINE GUIDE:

DIVISION 9 > 09 24 00 > PORTLAND CEMENT PLASTERING

One Coat Fiberglass Reinforced Stucco (FRS) >> Product No. 1200-80-Sanded, 1216-93-Concentrated



DESCRIPTION >> PRIMARY USE

QUIKRETE® One Coat Fiberglass Reinforced Stucco is a contractor grade one-coat stucco designed for use over plywood or OSB sheathing and exterior insulation wall panel systems. It is applied at 3/8" (9.4 mm) to 1/2" (12.9 mm) thickness to substrates of expanded polystyrene (EPS) insulation board, fiberboard, plywood, oriented strand board (OSB) or gypsum sheathing on exterior walls of wood or steel stud construction. It achieves a one-hour fire rating when applied over the combination of OSB and EPS foam and plywood and EPS foam. It is available in both sanded and concentrated formulations.

Compressive strength, ASTM C109

28 days	2020 psi (13.9 MPa)
---------	---------------------

Flexural strength, ASTM C348

28 days	570 psi (3.9 MPa)
---------	-------------------

Tensile strength, ASTM C109

28 days	180 psi (1.2 MPa)
---------	-------------------

SIZE AVAILABILITY

Sanded:

- 80 lb (36 kg) bags
- 3000 lb (1562 kg) bulk bags

Concentrated:

- 80 lb (36 kg) bags
- 90 lb (40.8 kg) bags

Base Coat Stucco – Scratch & Brown Coat >> Product No. 1139



DESCRIPTION >> PRIMARY USE

QUIKRETE® Base Coat Stucco is a contractor grade pre-blended Portland cement based scratch and brown coat stucco mix. It exceeds the performance requirements of ASTM C926 for Portland cement based plaster. It may be used in:

- Scratch and brown coat in 3-coat stucco application
- Apply directly to masonry walls in a 2-coat stucco application
- May be trowel or spray applied

SIZE AVAILABILITY

- 80 lb (36.3 kg) bags
- 3000 lb (1362 kg) bulk bags

Base Coat Stucco with Water-Stop >> Product No. 1139-86



DESCRIPTION >> PRIMARY USE

QUIKRETE® Base Coat Stucco with Water-Stop is water resistant, contractor grade, pre-blended Portland cement based scratch and brown coat stucco mix. It complies with ASTM C926 requirements for base coat plasters. It may be used in:

- Scratch and brown coat in 3-coat stucco application
- Apply directly to masonry walls in a 2-coat stucco application
- May be trowel or spray applied

SIZE AVAILABILITY

- 80 lb (36.3 kg) bags



PRODUCT LINE GUIDE:

DIVISION 9 > 09 24 00 > PORTLAND CEMENT PLASTERING

Finish Coat Stucco >> Product No. 1201



DESCRIPTION >> PRIMARY USE

QUIKRETE® Finish Coat Stucco is a Portland cement based finishing plaster complying with ASTM C926 requirements for Type F Plaster. It is designed for use as a decorative finish over Portland cement base coats or QUIKRETE® One Coat Fiberglass-Reinforced Stucco (No. 1200). It is manufactured as a complete product requiring only the addition of water.

Compressive strength

7 days	900 psi (6.2 MPa)
28 days	1200 psi (8.2 MPa)

SIZE AVAILABILITY

- 80 lb (36.3 kg) bags
- 90 lb (41 kg) bags
- 3000 lb (1362 kg) bulk bags

COLORS

- Gray
- White
- Factory pre-blended additional colors available by special order
- Finish Coat Stucco can be colored with QUIKRETE® Stucco and Mortar Color (No. 1319) to the mixing water prior to the addition of the dry Finish Coat Stucco.

Liquid Stucco Swirl Finish >> Product No. 1320

Liquid Stucco Coarse Sand Finish >> Product No. 1321

Liquid Stucco Fine Sand Finish >> Product No. 1322



DESCRIPTION >> PRIMARY USE

QUIKRETE® Liquid Stucco is a trowel applied, ready-to-use moisture resistant decorative wall coating designed to coat unpainted, above-grade concrete, stucco and masonry surfaces for interior or exterior use. It is a proprietary, 100% acrylic co-polymer based textured finish coat. Once applied, the product is freeze/thaw stable.

TEXTURE TYPES

- Swirl Finish No. 1320-00
- Coarse Sand Finish No. 1321-00
- Fine Sand Finish No. 1322-00

SIZE AVAILABILITY

- 60 lb (27 kg) buckets

COLORS

- White
- Can be colored with QUIKRETE® Liquid Stucco Color (No. 1323) which is available in 20 standard colors

