



# HardScapes®

by **QUIKRETE®**

**ADVANCED FORMULA**

## POLYMERIC JOINTING SAND

**High Performance Stabilizing Sand For Joints Up To 2" Wide**



- Heavy Duty Formula Ideal For High Traffic Areas
- Resists Erosion
- Non Staining
- Resists Weed Growth and Insects
- Designed For Commercial and Residential Use
- For New Joints or Replacement of Existing Joints
- Sets in Temperatures Above 35° F (2° C)



### Polymeric Jointing Sand Calculator

Square Feet (M2)	16 (1.5)	64 (5.9)	100 (9.2)	144 (13.3)	400 (37.2)
1/4" (6 mm) thick - # of 50 lb (22.7 kg) bags	1	2	3	4	10
1/2" (12 mm) thick - # of 50 lb (22.7 kg) bags	1	3	5	7	18
3/4" (19 mm) thick - # of 50 lb (22.7 kg) bags	1	4	7	9	26
1" (25 mm) thick - # of 50 lb (22.7 kg) bags	2	5	8	11	32
2" (51 mm) thick - # of 50 lb (22.7 kg) bags	2	8	13	19	50

\*Based on standard 2" x 4" x 8" (50 mm x 100 mm x 200 mm) brick. Usage will be different for other brick sizes. All yields are approximate and do not include allowance for waste, uneven joint width, etc.



Item No.	Package Size	Quantity	UPC
1175-56	50 lb (22.7 kg)	64 per pallet	0-39645-11749-1

For more information visit [www.quikrete.com](http://www.quikrete.com).