



HardScapes
by **QUIKRETE**

ADVANCED FORMULA

POLYMERIC JOINTING SAND

High Performance Stabilizing Sand For Joints Up To 2" Wide

Polymeric Jointing Sand (No. 1175-56) is an advanced formula, polymer-modified graded sand for filling joints up to 2" wide between interlocking pavers, brick, natural stone and concrete slabs. Once swept into the paver joints and dampened with a water mist it hardens, locking pavers into place.



SWEEP IT!



MIST IT!

- Heavy Duty Formula Ideal For High Traffic Areas
- Resists Erosion
- Non Staining
- Resists Weed Growth and Insects
- Designed For Commercial and Residential Use
- For New Joints or Replacement of Existing Joints
- Sets in Temperatures Above 35° F (2° C)



Concrete & Brick Pavers



Natural Stone

Polymeric Jointing Sand Calculator

Square Feet (M2)	16 (1.5)	64 (5.9)	100 (9.2)	144 (13.3)	400 (37.2)
1/4" (6 mm) thick - # of 50 lb (22.7 kg) bags	1	2	3	4	10
1/2" (12 mm) thick - # of 50 lb (22.7 kg) bags	1	3	5	7	18
3/4" (19 mm) thick - # of 50 lb (22.7 kg) bags	1	4	7	9	26
1" (25 mm) thick - # of 50 lb (22.7 kg) bags	2	5	8	11	32
2" (51 mm) thick - # of 50 lb (22.7 kg) bags	2	8	13	19	50

*Based on standard 2" x 4" x 8" (50 mm x 100 mm x 200 mm) brick. Usage will be different for other brick sizes. All yields are approximate and do not include allowance for waste, uneven joint width, etc.

Visit www.quikrete.com for more landscaping ideas.