

PowerLoc™ Jointing Sand No. 1150-47

Uses:

QUIKRETE[®] PowerLoc[™] Jointing Sand is suitable for sweeping into paving stone joints of ½" (12mm) or less in width. Once placed and dampened PowerLoc, hardens to lock pavers in place.

Composition and materials:

QUIKRETE® PowerLoc Jointing Sand is a blend of fine sand and special additives.

Availability/Yield:

QUIKRETE® PowerLoc Jointing Sand is available in 50 pound (22.7 Kg) bags. Coverage of QUIKRETE® Polymer Modified Joint Locking sand will vary by joint design. Approximate coverage is 50-55 square feet of tumbled pavers or 85-90 square feet of regular pavers.

Applications:

Preparatory Work

Prepare the paver base with QUIKRETE® Patio Paver Base Sand to provide proper drainage characteristics. Pavers must have a clean and dry surface for proper application.

Installation

- Using a broom, sweep QUIKRETE® PowerLoc Jointing Sand into the paver joints, filling completely.
- Compact sand into joint spaces as thoroughly as possible
- Remove excess sand from the paver surface prior to dampening.

Dampening

With a garden hose, apply a gentle fine mist to the filled joints. Repeat dampening at regular intervals for the first hour after placement.

NOTE: Avoid over-watering joints. Maintain the joint in a damp condition without flooding or washing the Joint Locking Sand away.

Precautions

Protect from freezing. Plastic sheeting and insulation blankets should be used if

The QUIKRETE® Companies, Inc.

One Securities Centre 3490 Piedmont Road, Suite 1300 Atlanta, GA 30305 404.634.9100 temperatures are expected to fall below 50°F (4°C) during the first 48 hours.

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suit-able for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30329. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages