0

0

0

HEALTH

FLAMMABILITY

PHYSICAL HAZARD

PERSONAL PROTECTION



CEMENT & CONCRETE PRODUCTS"

Expansion Joint Strips

MATERIAL SAFETY DATA SHEET (Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE[®] Companies One Securities Centre 3490 Piedmont Road, Suite 1300 Atlanta, GA 30329

QUIKRETE[®] Product Name

QUIKRETE[®] EXPANSION JOINT

Emergency Telephone Number (770) 216-9580 Information Telephone Number (770) 216-9580

MSDS U1 Revision: Feb-07

> <u>Code #</u> 6917

PRODUCT USE: FILLER MATERIAL FOR EXPANSION JOINTS IN CONCRETE CONSTRUCTION

SECTION II - HAZARD IDENTIFICATION

Route(s) of Entry: Inhalation if dust is generated during fabrication Acute Exposure: Temporary irritation of eyes, nose, throat or lungs Chronic Exposure: Not expected Carcinogenicity: Non-carcinogenic Signs and Symptoms of Exposure: None known Medical Conditions Generally Aggravated by Exposure: None known Chronic Exposure: None Known Medical Conditions Generally Aggravated by Exposure: None known

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION				
Hazardous Components	CAS No.	PEL (OSHA) mg/M ³	TLV (ACGIH) mg/M ³	
Cellulose (respirable) Asphalt-fume	9004-34-6 8052-42-4	5 none	5 5	
Clay (respirable)	None	5	5	
Carbon Black	1333-86-4	3.5	3.5	

SECTION IV – First Aid Measures

Eyes: Immediately flush eye thoroughly with water for at least 15 minutes.

ONE SECURITIES CENTRE, 3490 PIEDMONT ROAD, SUITE 1300, ATLANTA, GA 30305

TEL 404-634-9100



CEMENT & CONCRETE PRODUCTS™

Skin: Wash skin with cool water and pH-neutral soap or a mild detergent.

Inhalation: Remove person to fresh air. Seek medical help if coughing and other symptoms do not subside.

Other: This product is not expected to present health hazards under normal use.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flammability: Combustible Auto-ignition Temperature: Not Applicable Flash Points: Not Applicable

SECTION VI – ACCIDENTAL RELEASE MEASURES

Follow normal housekeeping procedures.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

None

SECTION VIII – EXPOSURE CONTROL MEASURES

Engineering Controls: Local exhaust can be used, if necessary, to control airborne dust levels. **Personal Protection:** As necessary to prevent skin irritation and to prevent foreign bodies from entering the eyes.

Exposure Limits: Consult local authorities for acceptable exposure limits.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance: Black board with a slight petroleum odor

Specific Gravity:	~0.3
Boiling Point:	Not Applicable
Vapor Density:	Not Applicable

Melting Point: Vapor Pressure: Evaporation Rate:

Not Applicable Not Applicable Not Applicable

SECTION X - REACTIVITY DATA

Stability: Stable under normal atmospheric conditions.

Incompatibility (Materials to Avoid): Avoid contact with strong oxidizing agents such as perchloric or nitric acids, etc.

Hazardous Decomposition or By-products: Thermal oxidative decomposition of asphalt can produce carbon monoxide; various aliphatic hydrocarbons and hydrogen sulfide. Inhalation of carbon monoxide and hydrogen sulfide produces tissue hypoxia (insufficient oxygen). Inhalation of aliphatic hydrocarbons can result in asphyxia.

Hazardous Polymerization: Will Not Occur.



Cement & Concrete Products™

Unusual Fire & Explosion Hazards: May be prone to smolder longer than wood after flames have extinguished

Special Firefighting Procedures: Since burning may produce toxic fumes, wear a self-contained breathing apparatus (SCBA) with a full facepiece. Wear protective clothing if asphalt is molten. **Special Precautions:** Use of a high-speed rotary cutting tool may create excessive dust. Avoid dust inhalation with adequate ventilation and the use of respiratory protection. Cellulose dust can present an explosion hazard if a high concentration dust cloud contacts an ignition source.

SECTION XI – TOXICOLOGICAL INFORMATION

The U. S.S National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Administration (OSHA) do not designate carbon black as a carcinogen. The American Conference of Governmental Industrial Hygienists (ACGIH) classifies carbon black as 4A, Not Classifiable as a Human Carcinogen. Components of this product are not listed as toxic chemicals under Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA). The U.S. National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends only carbon blacks with polycyclic aromatic hydrocarbons (PAH) levels greater than 0.1% be considered suspect carcinogens. The carbon black used in this product contains less than 0.1% of PAH. The International Agency for Research on Cancer (IARC) classifies carbon black, as Group 2B, carbon black is possibly carcinogenic to humans, based on rat inhalation studies. In the Monograph 65, issued in 1996, IARC reevaluated carbon black and concluded, "There is inadequate evidence for the carcinogenicity of carbon black".

SECTION XII – ECOLOGICAL INFORMATION

Ecotoxicity: Not Available BOD5 and COD: Not Available Products of Biodegradation: Not available Toxicity of the Products of Biodegradation: Not available Special Remarks on the Products of Biodegradation: Not available

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method: The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is <u>not</u> classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302).

SECTION XIV – TRANSPORT INFORMATION

DOT/UN Shipping Name: Non-regulated **DOT Hazard Class:** Non-regulated **Shipping Name:** Non-regulated Non-Hazardous under U.S. DOT and TDG Regulations



CEMENT & CONCRETE PRODUCTS™

SECTION XV – OTHER REGULATORY INFORMATION

US OSHA 29CFR 1910.1200: Considered non-hazardous under this regulation

SARA (Title III) Sections 311 & 312: Not listed

SARA (Title III) Section 313: Not subject to reporting requirements

TSCA (May 1997): All components are on the TSCA inventory list

Federal Hazardous Substances Act: Is a hazardous substance subject to statues promulgated under the subject act

Canadian Environmental Protection Act: Not listed

Canadian WHMIS: Considered to be a non-hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This product has been classified according to the hazard criteria of the Controlled Products Regulation (CPR). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

SECTION XVI – OTHER INFORMATION				
HMIS-	III: Health –	 0 = No significant health risk 		
		1 = Irritation or minor reversible injury possible		
		2 = Temporary or minor injury possible		
		3 = Major injury possible unless prompt action is taken		
		4 = Life threatening, major or permanent damage possible		
	Flammability-			
		 Material must be preheated before ignition will occur 		
		2 = Material must be exposed to high temperatures before ignition		
		3 = Material capable of ignition under normal temperatures		
		4 = Flammable gases or very volatile liquids; may ignite spontaneously		
	Physical Hazard-	0 = Material is normally stable, even under fire conditions		
		1 = Material normally stable but may become unstable at high temps		
		2 = Materials that are unstable and may undergo react at room temp		
		3 = Materials that may form explosive mixtures with water		
		4 = Materials that are readily capable of explosive water reaction		
Abbre	viations:			
	ACGIH	American Conference of Government Industrial Hygienists		
	CAS	Chemical Abstract Service		
	CERCLA	Comprehensive Environmental Response, Compensation & Liability Act		
	CFR	Code of Federal Regulations		
	CPR	Controlled Products Regulations (Canada)		
	DOT	Department of Transportation		
	IARC	International Agency for Research		
	MSHA	Mine Safety and Health Administration		
	NIOSH	National Institute for Occupational Safety and Health		
	NTP	National Toxicity Program		
	OSHA	Occupational Safety and Health Administration		
	PEL	Permissible Exposure Limit		



CEMENT & CONCRETE PRODUCTS™

RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TWA	Time-weighted Average
WHMIS	Workplace Hazardous Material Information System

Revision #07-01, supersedes all previous revisions. Created: 10/25/2006 Last Updated: February 7, 2007

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.