



**CEMENT & CONCRETE PRODUCTS™**

# BLACKTOP REPAIR

**PRODUCT NO. 8630-10, -15**

**DIVISION 3**

Concrete Accessories  
03 15 00

## PRODUCT DESCRIPTION

QUIKRETE® Blacktop Repair is a textured acrylic caulking material used to fill ¼" to ½" wide cracks in asphalt driveways and is colored to match blacktop.

## PRODUCT USE

QUIKRETE® Blacktop Repair is a water-resistant acrylic formula that stays flexible. It is textured to blend with blacktop surfaces, has minimal shrinkage, excellent adhesion, and is non-flammable.

## SIZES

• QUIKRETE® Blacktop Repair is packaged in 10 fl-oz (296 ml) caulking tubes and 5.5 fl-oz. (163 ml) squeeze tubes.

## INSTALLATION

### SURFACE PREPARATION

Surface must be clean, dry, free of grease, dust, or loose particles. Remove all loose stones and chips from the crack before filling.

### APPLICATION

- Cut tip of spout on angle to make a ¼" (6 mm) to ⅜" (9 mm) hole.
- Use cartridge in standard caulking gun. Apply by pushing cartridge tip over surface and forcing bead of Blacktop Repair deep into the crack. Apply no thicker than ⅜" (9 mm) at a time. On horizontal surfaces, deep cracks can be partially filled with sand prior to application.
- Blacktop Repair can be tooled to smooth the surface.
- Excess Blacktop Repair can be wiped off with a damp cloth.
- Wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F (4°C) for proper application.



## PRECAUTIONS

- Do not apply when temperatures are below 50°F (10°C) or if rain threatens or is predicted within 12 hours. Store between 35°F (2°C) and 100°F (38°C).
- May cause eye, skin and respiratory irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Use only with adequate ventilation. Ingestion may cause irritation.

## WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at [www.quikrete.com/product-warranty](http://www.quikrete.com/product-warranty) or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.

\* Refer to [www.quikrete.com](http://www.quikrete.com) for the most current technical data, SDS, and guide specifications  
Revised 08 September 2016