

CONCRETE & MASONRY HIGH GLOSS SEALER

PRODUCT NO. 8800-06, -08

PRODUCT DESCRIPTION

QUIKRETE® Concrete & Masonry High Gloss Sealer is a water-based, high gloss, acrylic clear sealer designed to waterproof, seal and enhance the color of decorative concrete, masonry, pavers, brick and natural stone surfaces. The high gloss sealer repels water and protects from oil, gasoline, grease, salts, acids, household chemicals, food stains and is UV resistant. For interior or exterior use.

PRODUCT USE

QUIKRETE® Concrete & Masonry High Gloss Sealer is a highly water resistant clear, glossy coating designed to water proof, seal and enhance the color of decorative concrete, masonry, pavers, brick and natural stone surfaces. QUIKRETE® High Gloss Sealer is UV Resistant.

SIZES

- 1 gal (3.8 L) bottle
- 5 gal (19 L) pail

COVERAGE

Apply at 200-400 sq ft per gallon (18-37 M²). Coverage will depend on surface texture and porosity.

PHYSICAL PROPERTIES

Typical physical properties of QUIKRETE® High Gloss Sealer are identified in Table 1.

TABLE 1 TYPICAL PHYSICAL PROPERTIES

Solids Content	25% wt.
Drying time (50-90° F / 10-32°C)	Approx. 2 hour
Volatile Organic Compound (VOC)	90 g/L *
<i>*less water and exempt compounds; Meets VOC requirements in all locations; Do not thin.</i>	

INSTALLATION

SURFACE PREPARATION

New concrete: Allow a minimum of 30 days for new concrete to cure before applying High Gloss Sealer.

Existing surfaces: Surface must be clean and dry. Oil stains, dirt and other contaminants must be removed. Use QUIKRETE® Concrete and Asphalt Cleaner (No. 8601) or QUIKRETE Oil Stain Remover (No. 8670-06) to properly prepare the surface. Unsound or flaking concrete should be removed or repaired.

DIVISIONS 3 7 9

Maintenance of Concrete
03 01 00
Water Repellent & Sealant
07 19 00
Coating for Concrete &
Masonry 09 98 00



Previously sealed surfaces: Surface must be clean, porous and able to accept additional sealer. Do not use this product on non-porous, sealed or painted surfaces. To test, place drops of water on the surface. If the water is absorbed, the surface is porous enough to accept the sealer. Do not coat over solvent or oil based paints and stains.

APPLICATION

WEAR IMPERVIOUS GLOVES, such as nitrile. QUIKRETE® Concrete & Masonry High Gloss Sealer is ready-to-use and can be applied with a roller, brush or garden sprayer. Best appearance is obtained with a high density foam roller. Apply in a uniform thickness to obtain coverage of 200-400 sq. ft (18-37 M²) per gallon. Coverage will vary depending on surface texture and porosity. A second coat can be applied after 2 hours. Apply second coat perpendicular to the first. Wipe off excess sealer from surface before it dries. Clean up with warm, soapy water.

PRECAUTIONS

- Apply only if air and surface temperatures are 50°F - 90°F (10°C - 32°C)
- Do not apply if raining, heavy dew or temperatures below 50°F (10°C) are expected within 24 hours. Do not use to seal areas prone to standing water. Resists and repels water. Does not replace an exterior membrane for waterproofing basement walls. Keep from freezing. Do not apply more than recommended amount. Do not recoat.
- Solvents and cleaners containing solvents, such as pine or citrus, will discolor.
- For more information, refer to Safety Data Sheet (SDS) online at www.quikrete.com

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Store between 40°F and 100°F (4°C and 38°C). In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of used absorbent, container and/or unused contents in accordance with local, state and federal regulations.

WARNING: May cause eye and skin irritation. Avoid breathing spray mist or dust generated in sanding. If using indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for

use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use.

WARRANTY

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.