



Concrete Repair

No. 8620-10, 8620-13

QUIKRETE® Concrete Repair is a superior acrylic latex formulation for crack repair in concrete, including concrete, stucco or masonry walls, sidewalks, patios, driveways.

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces.
- weather resistant
- Excellent Adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

Uses: Repairs and fills cracks up to ½" (12 mm) wide in concrete, masonry, stucco, sidewalks, patios, and driveways.

Packaging: QUIKRETE® Concrete Repair is available in 10-fl. oz. (296 ml) caulking tubes and 5.5-fl. oz (163ml) squeeze tubes.

Coverage:

- ◇ 10 fl-oz. tubes yield about 24 lineal ft. (7.4 M) for 1/4" (6 mm) diameter bead or 12 lineal ft. (3.7 M) for a 3/8" (9 mm) diameter bead.
- ◇ 5.5 fl-oz. Tubes yield about 12 lineal feet (3.7 M) at a 1/4" (6 mm) diameter bead.

Directions: Surface must be clean, dry, free of grease, dust, or loose particles. Remove all loose stones and chips from the crack before filling.

(1) Cut tip of spout on angle to make a ¼" (6 mm) to 3/8" (9 mm) hole. (2) Use cartridge in standard caulking gun. Apply by pushing cartridge tip over surface and forcing bead of Concrete Repair deep into the crack. Apply no thicker than 3/8" (9 mm) at a time. On horizontal surfaces, deep cracks can be partially filled with sand prior to application. (3) Concrete Repair can be tooled to smooth the surface. (4) Excess Concrete Repair can be wiped off with a damp cloth. (5) Wait at least 24 hours before painting. Use latex paints only. Air and surface

temperature should be above 40°F/4°C for proper application. (6) Do not apply if rain threatens or is predicted within 12 hours.



Caution: May cause eye, skin and respiratory irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Use only with adequate ventilation. Ingestion may cause irritation. Store between 35 °F (2°C) and 100 °F (38°C).

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30305. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies, Inc.

One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305
404.634.9100