



EFFLORESCENCE & RUST REMOVER

PRODUCT NO. 8675-33

PRODUCT DESCRIPTION

QUIKRETE® Efflorescence & Rust Remover (No. 8675-33) is a concentrated, water based formula for removing efflorescence and rust stains from concrete, paver, masonry, brick and stucco surfaces. The product also restores and enhances the natural color of the surface prior to the application of sealers.

PRODUCT USE:

Removes efflorescence & rust from horizontal and vertical concrete, pavers, brick, masonry and stucco surfaces

- Solvent Free
- Low odor
- Easy to rinse
- Heavy-duty commercial product

SIZES:

- Gallon (3.8 L)

Coverage:

- 100-200 sq. ft. (9.3-18.6 sq. M) per gallon (3.8 L)

APPLICATION

1. **WEAR IMPERVIOUS GLOVES, such as nitrile.** Protect eyes, skin and clothes. Wear rubber boots.
2. Sweep and remove all soil and debris from the surface.
3. Dilute product in a plastic container to a 1:4 dilution. Brush or spray diluted material onto surfaces. Spray carefully. More concentrated dilutions are possible (1 part Efflorescence & Rust Remover to 3, 2, or 1 part water). **Exercise caution** especially with more concentrated dilutions as they may cause etching, particularly when left in contact for longer times.
4. Allow the material to work for one minute.
5. For heavy efflorescence, scrubbing with a medium to stiff bristled nylon brush will improve removal. Rinse thoroughly with water.
 - Efflorescence & Rust Remover is designed to provide effective and easy efflorescence removal while protecting against etching when applied and rinsed appropriately.
 - Efflorescence & Rust Remover should be test applied in an inconspicuous spot in order to optimize the application technique and to evaluate the effect, before treating the entire area.

DIVISION 3

Concrete Restoration & Cleaning
03 90 00
Concrete Cleaner - 03 91 00
Unit masonry Cleaner – 04 93 00



PRECAUTIONS

- **WEAR IMPERVIOUS GLOVES, such as nitrile,** which are acid resistant. Wear safety glasses when handling product. Avoid prolonged contact with skin or inhalation of vapors. Use with adequate ventilation. Contains salt of organic acid. Wear rubber boots to protect feet. Slippery when wet.
- Contact with product may damage clothing.
- Do NOT mix with bleach, cleaners or other chemicals; chemical reactions may occur and produce poisonous gas.
- **PREVENT RUN-OFF.** This heavy duty product is not compatible with lawns and plants. Rinsing with large quantities of water dilutes the effect. Take appropriate precautions for vertical applications.
- Prevent contact with aluminum and other metals. Protect all non-concrete surfaces.
- Protect from freezing.
- For walls, take care to prevent dripping or streaking on the surface below.
- VOC = 0.21 g/L per EPA Method 24; Vapor Pressure of VOC <0.76 mm of Hg @ 20° C; Meets VOC requirements in all locations.
- For more information, refer to Safety Data Sheet (SDS) online at www.quikrete.com

WARRANTY

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.