



CEMENT & CONCRETE PRODUCTS™

MASON SAND

PRODUCT NO. 1952

PRODUCT DESCRIPTION

QUIKRETE® Mason Sand is suitable for field-preparation of mortar.

PRODUCT USE

A washed, properly graded fine masonry sand.

Use for:

Mix with QUIKRETE® Portland Cement & Hydrated Lime - Type S or with QUIKRETE® Masonry Cement to make Base Type N or Type S mortars.

To make mortar, mix QUIKRETE® Mason Sand with QUIKRETE® Portland Cement and QUIKRETE® Hydrated Lime - Type S or QUIKRETE® Portland-Lime Cement in accordance with ASTM C 270. Alternately, mix QUIKRETE® Mason Sand with QUIKRETE® Masonry Cement in accordance with ASTM C270.

Meets ASTM C144 specifications

SIZES

- QUIKRETE® Mason Sand - 50 lb (22.7 kg) bags

YIELD

- Each 50 lb (22.7 kg) bag of QUIKRETE® Mason Sand contains approximately 0.6 cu ft (17L) of sand by volume

PRECAUTIONS

- Not suitable for sandblasting

WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.

DIVISION 32

Aggregate
32 15 00



* Refer to www.quikrete.com for the most current technical data, SDS, and guide specifications