



CEMENT & CONCRETE PRODUCTS™

MASON SAND

PRODUCT No. 1961-56

DIVISION 32

32-15-00 Aggregate

PRODUCT DESCRIPTION

QUIKRETE® Mason Sand (No. 1961-56) is a washed, properly graded masonry sand meeting ASTM C144 which can be used for multiple purposes.

PRODUCT USE

QUIKRETE® Mason Sand is suitable for field preparation of masonry mortar as well as any other application that requires a washed and graded fine sand.

SIZES

QUIKRETE® Mason Sand is available in 50 lb (22.6 kg) bags.

YIELD

Each 50 lb (22.6 kg) bag of QUIKRETE® Mason Sand contains approximately 0.5 cu ft (14 L) of sand.

TECHNICAL DATA

- ASTM C144 Standard Specification for Aggregate for Masonry Mortar
- ASTM C270 Standard Specification for Mortar for Unit Masonry

INSTALLATION

MIXING

Mix with QUIKRETE® Portland Cement and Hydrated Lime Type S or SA in accordance with ASTM C270 to make Type S or Type N masonry mortar. Alternatively, mix with QUIKRETE® Masonry Cement in accordance with ASTM C270 to make Type S or Type N masonry mortar.

OTHER APPLICATIONS

- Fill joints between patio pavers, bricks, or stone.
- Mix with potting soil or use for other garden applications.

PRECAUTIONS

This sand is not suitable for sandblasting applications.



SAFETY

IMPORTANT: Read Safety Data Sheet carefully before using. **WEAR IMPERVIOUS GLOVES**, such as nitrile, mask, and eye protection.

WARNING: Contains crystalline silica sand. Prolonged or repeated inhalation of dust may cause lung damage or cancer. Do not breathe dust or swallow.

KEEP OUT OF REACH OF CHILDREN

WARRANTY

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured by or under the authority of The Quikrete Companies, LLC. © 2023 Quikrete International, Inc.