



Masonry Cement (Type S)

No. 1125-71

PRODUCT DESCRIPTION

Basic use: Used for making Type S masonry mortar, stuccos complying with ASTM C 926 or for any other application requiring Type S masonry cement. Type S masonry mortars are used for building structural masonry walls above or below grade.

Limitations: Masonry mortars must be blended with a specified amount of properly graded sand meeting ASTM C 144. For stucco applications use sand graded to comply with C 897. Follow design and construction practices as shown in ASTM C 926.

Composition and Materials: QUIKRETE® Masonry Cement, Type S is a high quality Masonry cement meeting ASTM C 91 Type S.

Sizes: QUIKRETE® Masonry Cement Type S is available in 70 lb (31.8 kg) bags.

Color: gray

Typical Mix Designs:

For masonry mortars: Mix 1 part QUIKRETE® Masonry Cement with 2.25 to 3 parts masonry sand in compliance with ASTM C 270.

For stuccos: Mix 1 part QUIKRETE® Masonry cement, Type S with 2.25 to 5 parts of plaster sand in accordance with ASTM C 926

Yield: Yield will vary with design. For example one bag of masonry cement mixed with 240 pounds (109 kg) of QUIKRETE® Mason's Sand will yield approximately 2.75 cu. ft. (78 L) of mortar and will lay about 46 standard block or 144 standard bricks.

TECHNICAL DATA

QUIKRETE® Masonry Cement, Type S complies with ASTM C 91 Type S.

The QUIKRETE® Companies, Inc.

One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305
404.634.9100

INSTALLATION

Before Application: Surfaces to receive masonry mortar should be dry or damp and clean and free of dirt loose debris, grease, oil or any other material which would reduce the bond of the mortar to the masonry.

Temperature: Do not use QUIKRETE® Masonry Cement at temperatures below 40 F (4.4°C) or if the temperature is expected to fall below freezing within 48 hr.

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30305. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.