

# MORTAR REPAIR

PRODUCT No. 8620

## PRODUCT DESCRIPTION

QUIKRETE® Mortar Repair is a sanded acrylic formula that adheres to brick, block, stone, and concrete surfaces.

## PRODUCT USE

QUIKRETE® Mortar Repair is a water-resistant acrylic formula that remains relatively flexible. It is textured and colored to give the appearance of masonry mortar. The product has minimal shrinkage, excellent adhesion, and is non-flammable. The unique square opening is ideal for filling 3/8" mortar joints.

## SIZES

- QUIKRETE® Mortar Repair - 10.1 oz (296 ml) caulking tubes and 5.5 oz (163 ml) squeeze tubes

## YIELD

- Each 10.1 fl oz. (296 ml) tube of QUIKRETE® Mortar Repair will fill a 3/8"x 3/8" (8 mm x 8 mm) mortar joint 14 ft. (4.3 M) long.

## INSTALLATION

Use to seal cracks and mortar joints in masonry walls.

- Joints must be clean, dry, and free of grease, dust, or loose particles. Remove all loose mortar from the joint before filling.
- Puncture seal inside the applicator tip. Use cartridge in standard caulking gun.
- Apply by pushing cartridge tip over surface and forcing bead of caulking into the opening. Apply no thicker than 3/8" (9 mm) in one application.
- Tip of applicator acts as a tool to smooth the surface.
- Excess can be wiped off with a damp cloth.

## DIVISION 4

Masonry Accessories  
04 05 23



- Can be painted after 24 hr. Use latex paints only.

## PRECAUTIONS

- Do not apply if rain threatens or is predicted within 12 hours. Not for use as a structural repair of badly damaged walls. Protect from freezing. Store between 35°F (2°C) and 100°F (38°C). Air and surface temperature should be above 40°F (4°C) for proper application.
- Do not use to fill control / expansion joints.

## CAUTION

May cause eye, skin, and respiratory irritation. Avoid breathing vapor and contact with eyes, skin, and clothing. Use only with adequate ventilation. Ingestion may cause irritation.

## WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies  
One Securities Centre  
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305  
(404) 634-9100 • Fax: (404) 842-1425

\* Refer to [www.quikrete.com](http://www.quikrete.com) for the most current technical data, MSDS, and guide specifications