

Cement & Concrete Products™

Concrete and Asphalt Cleaner

MATERIAL SAFETY DATA SHEET (Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE[®] Companies One Securities Centre 3490 Piedmont Road, Suite 1300 Atlanta, GA 30329

Emergency Telephone Number (770) 216-9580 Information Telephone Number (770) 216-9580

MSDS Y1 Revision: Feb-10

QUIKRETE[®] Product Name QUIKRETE[®] Concrete & Asphalt Cleaner

<u>Code #</u> 8601-01, 14



Product Use: Chemical cleaner for concrete and asphalt surfaces

SECTION II - HAZARD IDENTIFICATION

Route(s) of Entry: Skin, Ingestion

Acute Exposure: Direct eye-contact with material can cause irritation and possible corneal injury. **Chronic Exposure:** Prolonged exposure may cause slight irritation.

Carcinogenicity: Non-carcinogenic

Carcinogenicity Listings: Not applicable

Signs and Symptoms of Exposure: None known

Medical Conditions Generally Aggravated by Exposure: None known

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION				
Hazardous Components	CAS No.	<u>PEL (OSHA)</u>	TLV (ACGIH)	
<u></u>		mg/M ³	mg/M ³	
Glycol Ether	34590-94-8	Not Established	100 ppm	
Sodium Hydroxide	1310-73-2	2	2	
SECTION IV – First Aid Measures				

Eyes: Immediately flush eye thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call physician immediately.

ONE SECURITIES CENTRE, 3490 PIEDMONT ROAD, SUITE 1300, ATLANTA, GA 30305

TEL 404-634-9100



CEMENT & CONCRETE PRODUCTS™

Skin: Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment if irritation or inflammation develops or persists. Seek immediate medical treatment in the event of burns.

Inhalation: Remove to fresh air. Seek immediate medical attention if difficulty in breathing. **Ingestion:** If swallowed, give two glasses of water and induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flammability: Noncombustible and not explosive. Auto-ignition Temperature: Not Applicable Flash Points: Glycol Ether has a flash point of 208°F (98°C) Unusual Fire and Explosive Hazards: None

SECTION VI – ACCIDENTAL RELEASE MEASURES

If spilled, soak with absorbent material, flush remainder with water. Flush to sewer if permitted by applicable local, state and federal regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Store in a cool place; avoid freezing to preserve product utility.

SECTION VIII – EXPOSURE CONTROL MEASURES

Engineering Controls: Product is recommended for outdoor use only. No respiratory protection is required if ventilation is adequate. Avoid prolonged breathing of fumes.

Personal Protection: Use waterproof or chemical resistant gloves; wear safety glasses with side shields.

Exposure Limits: Consult local authorities for acceptable exposure limits.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance: Clean blue liquid with sassafras odor Solubility in Water: infinitely dilutable Boiling Point: 212°F (100°C) Freezing Point: ~30°F (-1°C)

SECTION X - REACTIVITY DATA

Stability: Stable.

Incompatibility (Materials to Avoid): Strong oxidizing agents

Hazardous Decomposition or By-products: Thermal decomposition may yield carbon monoxide and carbon dioxide.

ONE SECURITIES CENTRE, 3490 PIEDMONT ROAD, SUITE 1300, ATLANTA, GA 30305

TEL 404-634-9100



CEMENT & CONCRETE PRODUCTS™

Hazardous Polymerization: Will Not Occur.

SECTION XI – TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, Ingestion Toxicity to Animals: None known Chronic Effects on Humans: None known Special Remarks on Toxicity: Not Available

SECTION XII – ECOLOGICAL INFORMATION

Ecotoxicity: Not Available BOD5 and COD: Not Available Products of Biodegradation: Not available Toxicity of the Products of Biodegradation: Not available Special Remarks on the Products of Biodegradation: Not available

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method: The packaging may be landfilled and material may be flushed to sewer, if permitted by local, state and federal regulations. This product is <u>not</u> classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302).

SECTION XIV – TRANSPORT INFORMATION

DOT/UN Shipping Name: Non-regulated **DOT Hazard Class:** Non-regulated **Shipping Name:** Non-regulated Non-Hazardous under U.S. DOT and TDG Regulations

SECTION XV – OTHER REGULATORY INFORMATION

US OSHA 29CFR 1910.1200: Considered non-hazardous

SARA (Title III) Sections 311 & 312: Not applicable

SARA (Title III) Section 313: Not subject to reporting requirements

TSCA (May 1997): All components are on the TSCA inventory list

Federal Hazardous Substances Act: Considered non-hazardous

Canadian Environmental Protection Act: Not listed

Canadian WHMIS: Considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations (Class D2A, E- Corrosive Material) and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This product has been classified according to the hazard criteria of the Controlled Products Regulation (CPR). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

SECTION XVI – OTHER INFORMATION

CEMENT & CONCRETE PRODUCTS™

HMIS-II	ll: Health – Flammability-	 0 = No significant health risk 1 = Irritation or minor reversible injury possible 2 = Temporary or minor injury possible 3 = Major injury possible unless prompt action is taken 4 = Life threatening, major or permanent damage possible 0 = Material will not burn 1 = Material must be preheated before ignition will occur 2 = Material must be exposed to high temperatures before ignition 3 = Material capable of ignition under normal temperatures 4 = Flammable gases or very volatile liquids; may ignite spontaneously 	
	Physical Hazard-	 0 = Material is normally stable, even under fire conditions 1 = Material normally stable but may become unstable at high temps 2 = Materials that are unstable and may undergo react at room temp 3 = Materials that may form explosive mixtures with water 4 = Materials that are readily capable of explosive water reaction 	
Abbrev	viations:		
	ACGIH	American Conference of Government Industrial Hygienists	
	CAS	Chemical Abstract Service	
	CERCLA	Comprehensive Environmental Response, Compensation & Liability Act	
	CFR	Code of Federal Regulations	
	CPR	Controlled Products Regulations (Canada)	
	DOT	Department of Transportation	
	IARC	International Agency for Research	
	MSHA	Mine Safety and Health Administration	
	NIOSH	National Institute for Occupational Safety and Health	
	NTP	National Toxicity Program	
	OSHA	Occupational Safety and Health Administration	
	PEL	Permissible Exposure Limit	
	RCRA	Resource Conservation and Recovery Act	
		Superfund Amendments and Reauthorization Act	
		Threshold Limit Value	
		Time-weighted Average	
	WHMIS	Workplace Hazardous Material Information System	

Revision #07-01, supersedes all previous revisions. Created: 11/28/2006 Last Updated: February 23, 2010

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

ONE SECURITIES CENTRE, 3490 PIEDMONT ROAD, SUITE 1300, ATLANTA, GA 30305